

## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

## Listing of Claims:

1. (currently amended): Method for curtain coating a moving web (8) with at least one coating solution on a curtain (6), a lateral flow liquid (10) being supplied in a groove (13) having a width from 6mm to 8mm, perpendicular to the lateral extension of the curtain [~~(6)~~], on the lateral guides (7) having lower ends (14) with a downward protruding edge whose side facing the curtain forms an angle  $\beta$  with [~~the~~] a horizontal line facing the web and the two sides of the downwards protruding edge include an angle  $\alpha$ , which stabilize the curtain on both sides, wherein the total amount of the coating solution and the total amount of the lateral flow liquid are coated onto the moving web (8).
2. (original): Method for curtain coating a moving web (8) according to Claim 1, wherein the lateral flow liquid (10) is not separated from the coating liquid before both impinge on the moving web (8).
3. (previously amended): Method for curtain coating a moving web (8) according to Claim 1, wherein the distance between the protruding edge at the lower end (14) of the lateral guides (7) and the moving web (8) is from 0.05 mm to 3 mm.
4. (original): Method for curtain coating a moving web (8) according to Claim 1, wherein the distance between the lower end (14) of the lateral guides (7) and the moving web (8) is from 0.4 mm to 1.5 mm.
5. (currently amended): Device for curtain coating a moving web, comprising a curtain (6), two lateral guides (7) for

the curtain ~~[(6)]~~, exit slits (12) above the lateral guides to supply ~~[the]~~ a lateral flow liquid (10) perpendicular to the lateral extension of the curtain in a groove (13) having incorporated channels in the flow direction of the curtain and with a lower end (14) of the lateral guides having a downward protruding edge whose side facing the curtain forms an angle  $\beta$  with ~~[the]~~ a horizontal line facing the web and the two sides of the downwards protruding edge include an angle  $\alpha$ , wherein the width of the groove is from 6 mm to 8 mm ~~[has a rough surface structure]~~.

6. (canceled)

7. (canceled)

8. (canceled)

9. (original): Device according to Claim 5, wherein the angle  $\alpha$  between the two sides of the downwards protruding edge at the lower end (14) of the edge guide (7) is from 10° to 60°.

10. (canceled)

11. (original): Device according to Claim 5, wherein the angle  $\beta$  between the horizontal line and the side of the protruding edge facing the curtain at the lower end (14) of the edge guide (7) is from 30° to 90°.

12. (original): Device according to Claim 5, wherein the underside of the lower end (14) of the edge guide (7) has a hydrophobic surface with a free surface energy from 10 mNm to 60 mNm.

13. (original): Device according to Claim 5, wherein the underside of the lower end (14) of the edge guide (7) has a hydrophobic surface with a free surface energy from 20 mNm to 45 mNm.
14. (previously amended): Device according to Claim 13, wherein the surface of the underside of the lower end (14) of the lateral guide (7) is coated with polytetrafluoroethylene.
15. (canceled)
16. (previously amended): Device according to Claim 5, wherein the incorporated channels at the surface of the groove (13) have a sinusoidal or rectangular profile or a mixture of these profiles.
17. (previously amended): Device according to Claim 5, wherein the incorporated channels at the surface of the groove (13) have a depth from 1  $\mu\text{m}$  to 500  $\mu\text{m}$ .
18. (previously amended): Device according to Claim 5, wherein the incorporated channels at the surface of the groove (13) have a depth from 30  $\mu\text{m}$  to 100  $\mu\text{m}$ .